

### **Capacities**

112 Universal ports  
64 CO lines/72 station users

### **Chassis Measurements**

Base Cabinet  
Width: 11.9 in. (302 mm)  
Depth: 10.2in. (259 mm)  
Height: 14.6 in. (371 mm)  
Expansion Cabinet  
Width: 8.0 in. (203 mm)  
Depth: 10.2 in. (259 mm)  
Height: 14.6 in. (371 mm)

### **Weight**

Base cabinet 19.4 lbs. (8.8 Kg.)  
Expansion cabinet 15.2lbs. (6.9 Kg.)

### **Power Supply Unit (PSU)**

Initially Built In (one per cabinet)

### **Primary AC Power**

Input AC 120VAC, 4.0 amps maximum.  
AC Frequency Single-phase (48Hz - 62Hz)  
100 watts per cabinet (maximum)

### **Power Backup**

Two or four 12VDC external batteries (80 ampere-hours max.) with ABCS charger can provide power backup operation for 12 - 50 hours depending upon configuration (batteries and ABCS optional).

### **Chassis Installation**

Wall-mount (preferred) or Table top.

### **Compliance**

Safety: UL  
EMC: FCC Part 15 Class A (Subpart A)  
HAC and Volume Control: FCC Part 68  
Network safety: TIA-968-2-A

### **FCC Registration**

PBX: CJ6MUL-35931-PF-E

### **Toshiba IP5000-Series IP Telephones**

IP5022-SD full-duplex speakerphone with 10 programmable buttons and 4-line x 24-character LCD

IP5122-SD full-duplex speakerphone with 10 programmable buttons and 4-line x 24-character Backlit LCD

IP5122-SDC full-duplex speakerphone with 10 programmable buttons and 4-line x 24-character Backlit LCD and analog CO line interface

IP5132-SD full-duplex speakerphone with 20 programmable buttons and 4-line x 24-character Backlit LCD

IP5131-SDL full-duplex speakerphone with 10 programmable buttons and LCD key labels and 4-line x 24-character Backlit LCD

Hitachi WIP5000E-A wireless SIP telephone

### **Toshiba DP5000-Series Digital Telephones**

DP5008 single-line telephone with one programmable button

DP5018-S speakerphone with 10 programmable buttons

DP5022-SD speakerphone with 10 programmable buttons and 4-line x 24-character LCD

DP5122-SD speakerphone with 10 programmable buttons and 4-line x 24-character Backlit LCD

DP5032-SD speakerphone with 20 programmable buttons and 4-line x 24-

Hybrid: CJ6MUL-35930-MF-E  
Key: CJ6MUL-35929-KF-E

**Operating Temperature**  
32~104° F (0~40° C)

**Storage Temperature**  
-4~140° F (-20~60° C)

**Operating Humidity**  
20~80% relative humidity without condensation

**Voice Mail Compatibility**  
Strata Media Application Server,  
Stratagy ES, iES32, iES16, IVP8

**CO Line Compatibility**  
Analog: Loop or ground start, DID, E&M  
Digital: T1, ISDN PRI and BRI  
IP: Strata Net IP, SIP Trunks  
E911: CAMA and ISDN PRI

**System Administration**  
Browser-based unified administration of PBX and voice mail functions.  
eManager installation/maintenance for technicians and administrators.  
My Phone Manager personal administration for individual users.

**Standard System Features**  
Over 300 standard telephony features to provide the functionality you need.

character LCD

DP5132-SD speakerphone with 20 programmable buttons and 4-line x 24-character Backlit LCD

DP5130-SDL speakerphone with 10 programmable LCD-label buttons and 4-line x 24-character Backlit LCD

**Answer Position Options**  
20-button Add-On Module.  
60-button DSS/BLF Console.  
Strata Attendant Console uses PC as phone, or works with external IP-based handset.

**User Mobility Options**  
SoftIPT soft phone client on laptop or tablet PC via wi-fi W-LAN.  
SoftIPT soft phone client on PDA via wi-fi W-LAN.  
Wireless IP telephone support via wi-fi W-LAN.

**Advanced Application Options**  
Add valuable options like Voice Mail/Auto Attendant, Unified Messaging, Automated Speech Recognition, Text-to-Speech, Interactive Voice Response, Automatic Call Distribution and Reporting, Voice Over Internet Protocol, Strata Net multiple system networking, FeatureFlex adaptability/customization tools, and more.

**Multi-system Networking**  
Strata Net networking of up to 128 nodes via IP or ISDN PRI.

**Feature Customization**  
FeatureFlex adaptability tools for feature creation/customization.