

Strata CIX40 - Specifications

Capacities

4-11 Analog loop start CO lines with Caller ID
8-16 Digital telephones
4 Standard analog telephone ports
8-24 IP channels for connection of IP telephones or Strata Net networking
4-8 port, 40 hour voice recording storage, 374 mailbox voice mail

Cabinet Measurements

Height: 18.0 in.
Width: 12.2 in.
Depth: 3.5 in.
Weight: 6.6 lbs.

Strata CIX40 Power Specifications

Cabinet has built-in power supply
Input Voltage Rating: 90-264VAC
Input Current Rating: 1.5A Max.
Input Frequency: 50/60Hz
AC Adapter Output Voltage: +15V/4.0A
Voltage of Inside Power Switch: - 27.3V/+5.0V
Power Failure Backup: 1 or 2 HPFB-6
Grounding: Less than 1 Ohm Using Third Wire Ground

Power Backup

One or two Battery Back-up Modules (HPFB-6) can provide power backup operation for 1 - 2 hours, depending upon configuration, in case of AC power loss.

Chassis Installation

Wall-mount (preferred) or table top.

Compliance

Safety: UL
EMC: FCC Part 15 Class A (Subpart A)
HAC and Volume Control: FCC Part 68
Network safety: TIA-968-2-A

Toshiba IP5000-Series IP Telephones

IP5022-SD full-duplex speakerphone with 10 programmable buttons and 4-line x 24-character LCD

IP5122-SD full-duplex speakerphone with 10 programmable buttons and 4-line x 24-character Backlit LCD

IP5122-SDC full-duplex speakerphone with 10 programmable buttons and 4-line x 24-character Backlit LCD and analog CO line interface

IP5132-SD full-duplex speakerphone with 20 programmable buttons and 4-line x 24-character Backlit LCD

IP5131-SDL full-duplex speakerphone with 10 programmable buttons and LCD key labels and 4-line x 24-character Backlit LCD

Hitachi WIP5000E-A wireless SIP telephone

Toshiba DP5000-Series Digital Telephones

DP5008 single-line telephone with one programmable button

DP5018-S speakerphone with 10 programmable buttons

DP5022-SD speakerphone with 10 programmable buttons and 4-line x 24-character LCD

DP5122-SD speakerphone with 10 programmable buttons and 4-line x 24-character Backlit LCD

DP5032-SD speakerphone with 20 programmable buttons and 4-line x 24-

FCC Registration

Hybrid: CJ6MF03BDTCHS40, fully-protected multifunction systems
Key: CJ6KD03BDTCHS40, key systems for analog applications

Operating Temperature

32~104° F (0~40° C)

Storage Temperature

-4~140° F (-20~60° C)

Operating Humidity

20~80% relative humidity without condensation

Voice Mail Compatibility

GVPH1A Integrated Voice Mail
Strata Media Application Server

CO Line Compatibility

Analog: Loop start with Caller ID
IP: Strata Net IP, SIP Trunks

System Administration

Browser-based unified administration of PBX and voice mail functions.
eManager installation/maintenance for technicians and administrators.
My Phone Manager personal administration for individual users.

Standard System Features

Over 300 standard telephony features to provide the functionality you need.

character LCD

DP5132-SD speakerphone with 20 programmable buttons and 4-line x 24-character Backlit LCD

DP5130-SDL speakerphone with 10 programmable LCD-label buttons and 4-line x 24-character Backlit LCD

Answer Position Options

20-button Add-On Module.

60-button DSS/BLF Console.

Strata Attendant Console uses PC as phone, or works with external IP-based handset.

User Mobility Options

SoftIPT soft phone client on laptop or tablet PC

via wi-fi W-LAN.

SoftIPT soft phone client on PDA via wi-fi W-LAN.

Wireless IP telephone support via wi-fi W-LAN.

Advanced Application Options

Add valuable options like Voice Mail/Auto Attendant, Unified Messaging, Automated Speech Recognition, Text-to-Speech, Interactive Voice Response, Automatic Call Distribution and Reporting, Voice Over Internet Protocol, Strata Net multiple system networking, FeatureFlex adaptability/customization tools, and more.

Multi-system Networking

Strata Net networking of up to 128 nodes via IP.

Feature Customization

FeatureFlex adaptability tools for feature creation/customization.