

Capacities

672 Universal ports
264 CO lines/560 station users

Chassis Measurements

Base Cabinet
Width: 26.5 in. (673 mm)
Depth: 10.3in. (262 mm)
Height: 11.6 in. (295 mm)
Expansion Cabinet (maximum 6)
Width: 26.5 in. (673 mm)
Depth: 10.3 in. (262 mm)
Height: 9.8 in. (249 mm)

Weight

Base cabinet 19.4 lbs. (14.0 Kg.)
Expansion cabinet 29.0 lbs. (13.1 Kg.)

Power Supply Unit (PSU)

Initially Built In (one per cabinet)

Primary AC Power

Input AC 120VAC, 4.0 amps maximum.
AC Frequency Single-phase (48Hz - 62Hz)
180 watts per cabinet (maximum)

Power Backup

Two or four 12VDC external batteries (80 ampere-hours max.) with built-in charger can provide power backup operation for 2 - 29 hours depending upon configuration (batteries optional)..

Chassis Installation

19" Rack-mount, Wall-mount, or Floor-mount.

Compliance

Safety: UL
EMC: FCC Part 15 Class A (Subpart A)
HAC and Volume Control: FCC Part 68
Network safety: TIA-968-2-A

FCC Registration

Toshiba IP5000-Series IP Telephones

IP5022-SD full-duplex speakerphone with 10 programmable buttons and 4-line x 24-character LCD

IP5122-SD full-duplex speakerphone with 10 programmable buttons and 4-line x 24-character Backlit LCD

IP5122-SDC full-duplex speakerphone with 10 programmable buttons and 4-line x 24-character Backlit LCD and analog CO line interface

IP5132-SD full-duplex speakerphone with 20 programmable buttons and 4-line x 24-character Backlit LCD

IP5131-SDL full-duplex speakerphone with 10 programmable buttons and LCD key labels and 4-line x 24-character Backlit LCD

Hitachi WIP5000E-A wireless SIP telephone

Toshiba DP5000-Series Digital Telephones

DP5008 single-line telephone with one programmable button

DP5018-S speakerphone with 10 programmable buttons

DP5022-SD speakerphone with 10 programmable buttons and 4-line x 24-character LCD

DP5122-SD speakerphone with 10 programmable buttons and 4-line x 24-character Backlit LCD

DP5032-SD speakerphone with 20 programmable buttons and 4-line x 24-

PBX: CJ6MUL-35934-PF-E
Hybrid: CJ6MUL-35933-MF-E
Key: CJ6MUL-35932-KF-E

Operating Temperature

32~104° F (0~40° C)

Storage Temperature

-4~140° F (-20~60° C)

Operating Humidity

20~80% relative humidity without condensation

Voice Mail Compatibility

Strata Media Application Server,
Stratagy ES, iES32, iES16, IVP8

CO Line Compatibility

Analog: Loop or ground start, DID, E&M
Digital: T1, ISDN PRI and BRI
IP: Strata Net IP, SIP Trunks
E911: CAMA and ISDN PRI

System Administration

Browser-based unified administration of PBX and voice mail functions.
eManager installation/maintenance for technicians and administrators.
My Phone Manager personal administration for individual users.

Standard System Features

Over 300 standard telephony features to provide the functionality you need.

character LCD

DP5132-SD speakerphone with 20 programmable buttons and 4-line x 24-character Backlit LCD

DP5130-SDL speakerphone with 10 programmable LCD-label buttons and 4-line x 24-character Backlit LCD

Answer Position Options

20-button Add-On Module.

60-button DSS/BLF Console.

Strata Attendant Console uses PC as phone, or works with external IP-based handset.

User Mobility Options

SoftIPT soft phone client on laptop or tablet PC

via wi-fi W-LAN.

SoftIPT soft phone client on PDA via wi-fi W-LAN.

Wireless IP telephone support via wi-fi W-LAN.

Advanced Application Options

Add valuable options like Voice Mail/Auto Attendant, Unified Messaging, Automated Speech Recognition, Text-to-Speech, Interactive Voice Response, Automatic Call Distribution and Reporting, Voice Over Internet Protocol, Strata Net multiple system networking, FeatureFlex adaptability/customization tools, and more.

Multi-system Networking

Strata Net networking of up to 128 nodes via IP or ISDN PRI.

Feature Customization

FeatureFlex adaptability tools for feature creation/customization.